


## Performance

When used, these tubes are to be connected. See page 2-3.

Measuring range	2 to 5 ppm	5 to 120 ppm	120 to 312 ppm
Number of pump strokes	4 (400 mL)	2 (200 mL)	1 (100 mL)
Correction factor	0.4	1	2.6
Sampling time	8 min	4 min	2 min

Detecting limit : 0.5 ppm (4 pump strokes)  
 Colour change : White → Dark green  
 Operating conditions : Temperature 0 to 40 °C (32 to 104 °F) correction not used  
 Relative humidity 0 to 90 % correction not used  
 Relative standard deviation : 20 % (for 5 to 40 ppm), 15 % (for 40 to 120 ppm)  
 Tube quantity and number of tests per box : 10 tubes for 5 tests  
 Shelf life : 36 months

## Reaction principle



## Possible coexisting substances and their interferences

Substance	Concentration	Interference	Changes colour by itself to
Hexane	≦ 100 ppm	No	} No
Toluene	≦ 200 ppm	No	
Xylene	≦ 300 ppm	No	

Aromatic hydrocarbons other than benzene are trapped in the brown layer in the pretreatment tube. If the pretreatment reagent is entirely consumed (whole brown layer turns to dark brown), a higher reading will be given.

## Calibration gas generation

Diffusion tube method