


Performance

Measuring range	2 to 25 ppm	25 to 100 ppm
Number of pump strokes	4 (400 mL)	1 (100 mL)
Correction factor	1	4
Sampling time	2 min	30 sec
Detecting limit :	0.5 ppm (4 pump strokes)	
Colour change :	White → Yellow	
Operating conditions :	Temperature 0 to 40 °C (32 to 104 °F) correction not used Relative humidity 0 to 90 % correction not used	
Relative standard deviation :	10 % (for 2 to 5 ppm), 5 % (for 5 to 25 ppm)	
Tube quantity and number of tests per box :	10 tubes for 10 tests	
Shelf life :	36 months	

Reaction principle



Possible coexisting substances and their interferences

Substance	Concentration	Interference	Changes colour by itself to
Butadiene	≧ 5 ppm	} + (Bleaching)	Blackish brown
Alcohols	≧ 10 times		
Aldehydes	≧ 10 times		} No
Esters	≧ 10 times		
Ketones	≧ 10 times		

Other substance measurable with this detector tube

Substance	Correction	No. of pump strokes	Measuring range
Divinyl benzene	Factor : 0.6	3	1 to 15 ppm

Calibration gas generation

Diffusion tube method

Special note

A very low level concentration (0.2 to 4 ppm) of styrene can be measured by a Gastec special detector tube (No.124S) that is available with the Gastec Odorant Analysis System.