

# Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

## Acetic Acid

## CH<sub>3</sub>COOH

## SAA-2

TWA (TLV): 10 ppm

STEL (TLV): 15 ppm

Flammable Range: 4 – 19.9 %

### Specification:

	Extended	Standard	Extended
Measurement Range	Do not extend	2.5 - 50 ppm	Do not extend
No. of Pump Strokes		1 (100 mL)	
Volume Correction Factor (VCF)*		1.0	
Sampling Time	1 minute per pump stroke (100 mL)		
Color Change	Pink → Yellow		
Shelf Life	1 year		
Storage condition	Below 10°C (50°F)		
Calibration condition	Calibrated at 20°C (68°F) and 50% RH.		
Reaction Principle	CH <sub>3</sub> COOH + Base → Reaction product		
Relative standard deviation	± 10 %		

\* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

### Possible Interferences:

Compound	Concentration (ppm)	Interference	Colour change / Comments
Chlorine		+	Pink – White
HCl		+	Pink – Yellow
HCN	50	No	No Effect

### Correction for Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
Relative humidity	Not necessary between 10 - 90 %.



**Manufactured By:** Uniphos Envirotronic Pvt. Ltd.  
Nahuli (PO), Umbergaon (Tal.)  
Valsad (Dist), Gujarat, India – 396108

Rev.0812